

KIRBY VERTICAL MIXER

WP 1600



**EVEN MIX
FROM
START TO
FINISH**



CONTACT KIRBY AT
KIRBYMFG.COM OR BY
PHONE AT (209) 723-0778



VERTICAL MIXER FEATURES AND OPTIONS



RUBBER EXTENSION



CROSSFEED DISCHARGE



REAR DOOR



TWO SPEED COOLER



GREASE TENSIONER



SIDE DOOR



HYDRAULIC HOOKUPS



STEERABLE AXLE

Since 1946, Kirby has been obsessed with great products and great service. Our Vertical Mixers exemplify this commitment from end to end, creating a product that keeps the TMR the same on the first cow as it is on the last.

Isn't it time you got everything you needed?

MODEL WP 1600 SPECIFICATIONS

(ALL MEASUREMENTS IN INCHES)

Capacity (w/o belting)	1600 CU/FT
Overall Height	148
Overall Length	346
Overall Width	120
Discharge Height	32
Conveyor Width	36
Door Opening	51
Sidewall Thickness	1/4
Floor Thickness	1
PTO Requirements	1000 RPM
Minimum HP Requirement	200 HP

* Height (w/o belting & tandem axles)

** HP requirements may vary depending on commodities



**CONTACT KIRBY AT
KIRBYMFG.COM OR BY
PHONE AT (209) 723-0778**



STANDARD FEATURES

- 3/4" Thick Auger Flighting
- Nine Knives per Auger
- Hydraulic Front Discharge Door
- Heavy Duty Conveyor Chain
- Heavy Duty Tandem Axle
- Adjustable Hitch w/ HD Landing
- Two Rotational Hay Stops
- Scale and Mixer Installation
- L.H. Discharge Conveyor
- Tandem Axles / Steerable Axle
- Observation Ladder



**DIGISTAR
SCALE
SYSTEM**



OPTIONAL FEATURES

- Weigh System (Scalehead & Load Cells)
- Stainless Steel Lined Walls, Floor and Flighting
- Stainless Steel Crossfeed Conveyor
- 18" Slide Discharge Conveyor
- Righthand, Lefthand or Dual Discharge
- 10" Top Belting
- Hydraulic Rear Discharge Door
- Two Speed Gear Box
- Shift on the Fly Gearbox